

Declaration of Performance



Consort Ltd.
Units 1-4, Export Drive, Huthwaite,
Sutton-in-Ashfield, Nottinghamshire, NG17 6AF, UK
17

DoP No: 1- 31/10/17

VEKA Matrix FS Internally Glazed Casement Window, Glazed with Soft Coat, Warm edge spacer bar, Argon filled unit.
Intended for use in domestic or commercial refurbishment or new build application.

Annex ZA.1 of BS EN 14351-1:2006+A2:2016

Watertightness: NPD

Dangerous substances: None

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{k}$

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016.

Report No. WIL 330287 dated 29/07/2013 for Safety & Security friction hinges with built in restrictor – Exova UKAS accredited testing laboratory(No.0621) and EC notified body number (No 1104)

Thermal Transmittance calculation information provided by U value calculator notified body BSI 0086.

Simon Holt
Name (Print)

Head of Technical


Signed

31/10/2017