

# Declaration of Performance



Consort Ltd.  
Units 1-4, Export Drive, Huthwaite,  
Sutton-in-Ashfield, Nottinghamshire, NG17 6AF, UK  
17

DoP No: 17- 31/10/17

Consort Magnum Composite Door, Glazed with Soft Coat, Warm edge spacer bar, Argon filled unit.  
Intended for use in domestic or commercial refurbishment or new build application.

Annex ZA.1 of BS EN 14351-1:2006+A2:2016

Watertightness: NPD

Dangerous substances: None

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Not Fitted

Acoustic performance: NPD

Thermal transmittance:  $\leq 1.6 \text{ W/m}^2\text{k}$

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016.

Thermal Transmittance calculation information provided by Buildcheck Oracle U value calculator in line with EN10077- 1:2006 Verified by David Walker.

Simon Holt  
Name (Print)

Head of Technical

A handwritten signature in black ink, appearing to read 'S Holt', is written over a horizontal line.

Signed

31/10/2017