

Declaration of Performance



Consort Ltd.
Units 1-4, Export Drive, Huthwaite,
Sutton-in-Ashfield, Nottinghamshire, NG17 6AF, UK
17

DoP No: 2- 31/10/17

VEKA Matrix FS Internally Glazed Casement Window, Glazed with Non Soft Coat, and/or Aluminum spacer bar, Argon filled unit.
Intended for use in domestic or commercial refurbishment.

Annex ZA.1 of BS EN 14351-1:2006+A2:2016

Watertightness: NPD

Dangerous substances: None

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N when fitted (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 3.0 \text{ W/m}^2\text{k}$

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016.

Report No. WIL 330287 dated 29/07/2013 for Safety & Security friction hinges with built in restrictor – Exova UKAS accredited testing laboratory(No.0621) and EC notified body number (No 1104)

Thermal Transmittance calculation information provided by U value calculator notified body BSI 0086.

Simon Holt
Name (Print)

Head of Technical


Signed

31/10/2017