

Declaration of Performance



Consort Ltd.
Units 1-4, Export Drive, Huthwaite,
Sutton-in-Ashfield, Nottinghamshire, NG17 6AF, UK
17

DoP No: 3- 31/10/17

VEKA Matrix FS Internally Glazed Tilt and Turn Window, Glazed with Soft Coat, Warm edge spacer bar, Argon filled unit.
Intended for use in domestic or commercial refurbishment or new building applications.

Annex ZA.1 of BS EN 14351-1:2006+A2:2016

Watertightness: NPD

Dangerous substances: None

Resistance to wind load: EN 12211 Yes

Load-bearing capacity of safety devices: EN 14609 Pass

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{k}$

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016.

Report No. 228 7012530-1-10 IFT Certified. Hardware compliance certificate issued via Roto Frank AG.

Thermal Transmittance calculation information provided by U value calculator notified body BSI 0086.

Simon Holt
Name (Print)

Head of Technical

Signed

31/10/2017