

Declaration of Performance



Consort Ltd.
Units 1-4, Export Drive, Huthwaite,
Sutton-in-Ashfield, Nottinghamshire, NG17 6AF, UK
17

DoP No: 5- 31/10/17

VEKA Matrix FS Internally Glazed Reversible Window, Glazed with Soft Coat, Warm edge spacer bar, Argon filled unit.
Intended for use in domestic or commercial refurbishment or new build application.

Annex ZA.1 of BS EN 14351-1:2006+A2:2016

Watertightness: NPD

Dangerous substances: None

Resistance to wind load: NPD

Load-bearing capacity of safety devices: Pass, 350N (1)

Acoustic performance: NPD

Thermal transmittance: $\leq 1.6 \text{ W/m}^2\text{k}$

Radiation Properties: NPD

Air permeability: NPD

A Factory Production Control (FPC) system is established, documented and maintained in accordance with AVCP System 3 as per Annex ZA.2 of BS EN 14351-1:2006+A2:2016.

Report No. 181947. Clause 5.3 UKAS accredited test house Warrington apt, Tested to BS 6375-2:2009 for the load bearing capacity of safety devices.

Thermal Transmittance calculation information provided by U value calculator notified body BSI 0086.

Simon Holt
Name (Print)

Head of Technical

Signed

31/10/2017